

POL-E- FLAKE

LOST CIRCULATION

Description POL-E-FLAKE is a lost circulation product made from polyester film, which has been sized to 3/8". POL-E- FLAKE produces maximum mat sealing at the face of the well bore wall.

Properties Form: Flat Flakes Color: Transparent/Translucent
Odor: None Solubility: Insoluble in water
Water Requirement: None Bulk Density: 15 lb/ft³
Absolute Volume: 0.845 gal/lb

Application POL-E-FLAKE is inert and may be used in any common drilling fluid or cement system. POL-E FLAKE may be used in the mud system as a preventive filler while drilling a potential loss zone, and may be used combination with other lost circulation products to make a remedial plugging slurry. The recommended loading for POL-E- FLAKE should be 1/8 to 1/4 pound per sack of cement.

Compatibility POL-E-FLAKE is compatible with all cement systems. Not normally used in squeeze jobs.

Handling/Storage Avoid creating and inhaling dust. Fine particles or dust can cause eye irritation. Flush the affected area with water. If irritation persists seek medical attention. Use foam, dry chemicals, carbon dioxide or water spray as a fire extinguisher. Refer to Material Safety Data Sheet (MSDS) for handling and hazard data.

Packaging POL-E- FLAKE is shipped in 25 lb. bags.